

Lightweight HD-SDI Receiver

FEATURES AND BENEFITS

Perfect for director's monitor rigs, the Sidekick II allows you to receive a Bolt video feed from any 500, 1000 or 3000 model.

- SDI OUTPUT WITH 2 PIN POWER CONNECTOR
- SUPPORTS 20mhz CHANNELS WHEN PAIRED WITH BOLT 3000
- 300 FT RANGE
- COMPATIBLE WITH BOLT 500, 1000, 3000
- SUPPORTS TIMECODE AND START / STOP FLAGS
- BUILT-IN TEST PATTERN GENERATOR
- SUPER LIGHTWEIGHT AND COMPACT







	Bolt 3000	Bolt 1000	Bolt 500
Latency	<0.001 Seconds		
Range	3000ft	1000ft	500ft
Multicast	Up to 4pcs RX, per TX		
Size (TX)	24x66x102mm	26.5x66x109mm	24x66x102mm
Weight (TX/RX)	238g / 380g	262g / 480g	217g / 299g
Input /Output	a) HD-SDI only b) Dual (HDMI + HD-SDI)	a) HD-SDI only b) Dual (HDMI + HD-SDI)	a) HDMI only b) HD-SDI only c) Dual (HDMI + HD-SDI)
Screen	LCD screen on RX	LCD screen on RX	Field monitor control by OSD
Resolution / Frame Rate	Up to 1080p60		
TX HDMI / SDI Converter	YES		
No. of 20 MHz Channels*	24	0	0
No. of 40 MHz Channels**	11		
Rapid Reconnection	YES		
Sidekick II Compatible	YES		
Metadata Support	YES		
USB 3.0 GRAB Engine	YES		

- * 20MHz Channels cannot utilise interlaced PSF or 1080p60/50 frame rates at this time.
- $\ensuremath{^{**}}$ Based on USA channels. Channel availability may vary by region.

Contact us NOW for more details on the Teradek range of products.

Holdan Limited

Brookfield House, Brookfield Industrial Estate,
Peakdale Road, Glossop, Derbyshire SK13 6LQ United Kingdom

Phone: +44 (0)1457 851000 Email: sales@holdan.co.uk

www.holdan.co.uk



STRONGER, SMALLER AND EVEN MORE RELIABLE









SDI / HDMI Wireless Video Transceiver Set

FEATURES AND BENEFITS

LONGER RANGE

Transmit visually lossless video up to 3000ft with no delay.

20MHz CHANNELS

Use more than twice as many Bolts in one location or avoid interference like never before.

2 NEW DFS CHANNELS

Operate interference-free more often in the USA and Europe by making use of two newly introduced DFS channels.

20% SMALLER

Not just smaller, but lighter too allowing these models to integrate into any rig unnoticed.

MORE ROBUST THAN EVER BEFORE

Reach your Bolt's full range and potential with new software that provides the most robust wireless link we've ever created.

RAPID RECONNECTION

Reconnect times during a dropped link are now instantaneous once you move back into range.

BUILT IN HDMI TO SDI CONVERTER

Connect both your on-camera monitor and video source via the same device.

INDIVIDUAL IDENTITY

Easily identify which Bolt TX and RX work together with removable coloured top plates.

METADATA AND TIMECODE SUPPORT

3D LUTs

DUAL INPUTS/OUTPUTS

MULTICAST CAPABLE

MANUAL FREQUENCY SELECTION

USB 3.0 GRAB ENGINE INCLUDED





SDI / HDMI Wireless Video Transceiver Set

FEATURES AND BENEFITS

LONGER RANGE

Transmit visually lossless video up to 1000ft with no delay.

2 NEW DFS CHANNELS

Operate interference-free more often in the USA and Europe by making use of two newly introduced DFS channels.

20% SMALLER

Not just smaller, but lighter too allowing these models to integrate into any rig unnoticed.

MORE ROBUST THAN EVER BEFORE

Reach your Bolt's full range and potential with new software that provides the most robust wireless link we've ever created.

RAPID RECONNECTION

Reconnect times during a dropped link are now instantaneous once you move back into range.

BUILT IN HDMI TO SDI CONVERTER

Connect both your on-camera monitor and video source via the same device.

INDIVIDUAL IDENTITY

Easily identify which Bolt TX and RX work together with removable coloured top plates.

- METADATA AND TIMECODE SUPPORT
- Z 3D LUTs
- DUAL INPUTS/OUTPUTS
- MULTICAST CAPABLE
- MANUAL FREQUENCY SELECTION
- USB 3.0 GRAB ENGINE INCLUDED





SDI / HDMI Wireless Video Transceiver Set

FEATURES AND BENEFITS

LONGER RANGE

Transmit visually lossless video up to 500ft with no delay.

20% SMALLER

Not just smaller, but lighter too allowing these models to integrate into any rig unnoticed.

MORE ROBUST THAN EVER BEFORE

Reach your Bolt's full range and potential with new software that provides the most robust wireless link we've ever created.

RAPID RECONNECTION

Reconnect times during a dropped link are now instantaneous once you move back into range.

BUILT IN HDMI TO SDI CONVERTER

Connect both your on-camera monitor and video source via the same device

INDIVIDUAL IDENTITY

Easily identify which Bolt TX and RX work together with removable coloured top plates

